

HEDGE TRIMMER



Hedge Trimmer for Excavator and Backhoe loader

Hedge Trimmer is the perfect addition for excavators (2.5-8T) and Backhoe loaders, and offers a variety of motor sizes to suit your application. Attaching to a base machine provides extra-long cutting reach, gaining access to those taller trees and deeper hedges. The Hedge Trimmer is also ideal for cutting long grass and bushes.

Attaching the optional tooth extension bar provides a full 2.5m cutting length. This makes trimming more precise, efficient and will provide yet another way to expand the versatility of existing machines.

A neat and accurate cut,
every time.



FEATURES

- 1.5m cutting length
- Optional 1m cutting extension bar
- Cuts up to 40mm diameter
- Replace individual cutting teeth as required

SPECIFICATIONS

HEDGE TRIMMER - T150

50cc Motor Variant	
Suited to	: Excavators (2.5T - 4.5T)
Oil Pressure Range	: 28-220 Bar
Oil Flow Range	: 8-65 lpm
80cc Motor Variant	
Suited to	: Excavators (4.5T - 8T)
Oil Pressure Range	: 28-220 Bar
Oil Flow Range	: 8-66 lpm
100cc Motor Variant	
Suited to	: Excavators (8T) & Backhoe loader
Oil Pressure Range	: 28-220 Bar
Oil Flow Range	: 8-71 lpm
Max. Back Pressure	: 20 Bar
Hose Port Diameter	: 1/2" BSP
Cutting Length	: 1500 mm
Max. Cutting Diameter	: 40 mm
Dimensions	: 203 h x 1537 w x 270 d (mm)
Weight	: 69 kg

* Weight will vary subject to mounting type & extension



EXTENSION

Cutting Length	: 1 m
Combined Cutting Length	: 2.5 m
Max. Cutting Diameter	: 40 mm
Dimensions	: 118 h x 1192 w x 225 d (mm)
Weight	: 69 kg

OFFSET MOUNT

Max. Offset Distance	: 1.3 m
Cutting Angle	: Horizontal thru Vertical
Operating Voltage	: 12V
Dimensions	: 420 h x 245 w x 1510 l (mm)
Weight	: 56 kg

SUITABLE TO TRIM

- Grass
- Bushes
- Protruding Branches



Tata Hitachi Construction Machinery Company Private Limited

Registered Office: Jubilee Building, 45 Museum Road, Bangalore, India 560025
Telephone: +91 80 6695 3301 / 02 / 03 / 04 / 05 | Toll Free : 1800 121 6633
Email: info@tatahitachi.co.in | Website: www.tatahitachi.co.in | [f](#) [c](#) [in](#) [@](#) [v](#)

These specifications are subject to change without prior notice. The machine depicted may vary from the actual machine. Please contact our nearest office for latest specifications. Accessories shown here are not part of the standard equipment. Performance of the machine may vary with site and operating conditions encountered.

Authorised Dealership