

alicon *Super* SERIES

**POWERFUL &
PRODUCTIVE**

Now with

**12
Months**

Warranty*

* Conditions Apply



IMPROVED DURABILITY

- **Longer Piston & Damper** ensures better Anti-Blank Firing protection. ABF function helps to protect internal components.
- **Larger Through Bolt** protects against bolt breakage and extends component life.
- **Modified Front Cover:** Enhanced durability due to the larger diameter and integrated greasing port.

HIGHER PERFORMANCE

- **Enhanced Productivity** due to higher impact energy.
- **Larger Head Cap** containing more N₂ gas which helps to create higher impact energy.
- **Larger Chisel & Front Head** Improves front head life and the product performance.



Description	Unit	B145 Super+
Suitable Excavator	ton	10~15
Max. Hydraulic Input Power	kW	32.5
Control Valve Type	-	External Type
Operating Weight	kg	959
Overall Length	mm	2,263
Chisel Out Diameter	mm	105
Chisel Length	mm	975
Setting Pressure	bar	190
Working Pressure	bar	120~160
Oil Flow	L/min	90~110
Blow Rate (Long Stroke)	BPM	350~550
Back Head N ₂ Gas Pressure	kgf/cm ²	13
Adjustable BPM Valve	-	Available



Description	Unit	B215 Super+
Suitable Excavator	ton	18~25
Max. Hydraulic Input Power	kW	40
Control Valve Type	-	External Type
Operating Weight	kg	1,817
Overall Length	mm	2,841
Chisel Out Diameter	mm	135
Chisel Length	mm	1,300
Setting Pressure	bar	210
Working Pressure	bar	130~170
Oil Flow	L/min	110~160
Blow Rate (Long Stroke)	BPM	350~500
Back Head N ₂ Gas Pressure	kgf/cm ²	12
Adjustable BPM Valve	-	Available

Shape of Chisel

Classification	Major Contents		
Moil			Concrete, Rocks, Pavements, Slopes
Wedge			Trench, Slopes, Finishing
Blunt			Quarries
Conical			Concrete, Rocks, Pavements



Description	Unit	B235 Super+
Suitable Excavator	ton	18~25
Max. Hydraulic Input Power	kW	50
Control Valve Type	-	External Type
Operating Weight	kg	1,856
Overall Length	mm	2,841
Chisel Out Diameter	mm	140
Chisel Length	mm	1,300
Setting Pressure	bar	210
Working Pressure	bar	130~180
Oil Flow	L/min	130~170
Blow Rate (Long Stroke)	BPM	250~400
Back Head N ₂ Gas Pressure	kgf/cm ²	13
Adjustable BPM Valve	-	Available

Tata Hitachi Construction Machinery Company Private Limited

Registered Office: Jubilee Building, 45, Museum Road, Bengaluru – 560 025

Telephone: +91 80 6695 3301 / 02 / 03 / 04 / 05 | Toll Free: 1800 121 6633

Email: info@tatahitachi.co.in | Website: www.tatahitachi.co.in

Tata Hitachi Authorised Dealer: