

QUICK COUPLER



GTX



GTX QUICK COUPLER

The hydraulic GTX quick coupler is engineered to enhance machine productivity by enabling safe, fast and effortless attachment changes from the operator's cabin. Its compact, low-profile design improves breakout force and overall digging performance, ensuring maximum efficiency across applications.

FEATURES

- Optimised Low-Profile Design
- High-Strength Front Latch
- Heavy-Duty Lifting Eye
- ISO-Certified Safety Cylinder
- High-Strength Cast Frame



SPECIFICATIONS

GTX RANGE	Excavator Mass (T)	Coupler Mass (kg)	Pin Diameter (mm)	Min Pickup Width (mm)	Pin Pickup Range (mm)
Range 3	8 - 10	88 - 90	50 / 60	164 / 184	50: 273 - 312 60: 290 - 315
Range 4	11 - 14	185 - 193	60 / 65	216	60: 345 - 415 65: 355 - 420
Range 5	15 - 19	264 - 277	70 / 80	272	70: 370 - 465 80: 385 - 470
Range 6	20 - 22	330 - 347	80	302	430 - 520
Range 7	24 - 30	422 - 479	80 / 90	321	80: 440 - 510 90: 450 - 520
Range 8	30 - 36	585 - 704	90 / 100	340	90: 480 - 590 100: 495 - 595
Range 9	36 - 50	738 - 834	100 / 110	367 / 396	100: 525 - 625 110: 538 - 630



Maximum Performance
& Fuel Efficiency



Enhanced Safety



Higher Productivity
& Machine Versatility



Easy Installation
& Minimal Maintenance


Tata Hitachi Construction Machinery Company Private Limited

Registered Office: Jubilee Building, 45 Museum Road, Bangalore, India 560025
Telephone: +9180 66953301 / 02 / 03 / 04 / 05 | Email: info@tatahitachi.co.in



www.tatahitachi.co.in

1800 121 6633



OUR RANGE OF PRODUCTS



Mini Excavator



Construction Excavator



Backhoe Loader



Wheel Loader



Dump Truck



Mining Excavator

Authorised Dealership